



Features & Benefits

The Commercial Single Face Body has a hingeable frame that allows access to service the sign. The frame has provisions for Tension Clips, Corner Angles, Frame Braces and Corner Keys. The face material does not need to be hemmed and will not require grommets or double faced tape. It is available in Mill finish and Dark Bronze.



Answers to FAQ's

- Accepts up to 22 oz banner material
- Tension Clip placement - Tension clips are placed approximately 1-1/2" from the edge of the trimmed to size face material
- Tension Clip spacing - Every 6" on center
- Face material trim size - Add 1-1/2" to all four sides from the outside dimension of the assembled frame (Add a total of 3" of face material to both the height and width of the assembled frame)
- Visible opening - Deduct 4-1/2" from the cabinet height and width
- Add 1" to the direction of the lamps to allow for standard T12 bulbs to fit
- Recommended lamp spacing every 12" on center
- Frame Brace and Frame Support placement - Place every 36" on center horizontally and vertically
- The Tension Tool that is required for this frame is Part #5135

Optional Items

- 6" Cast Radius Corner, Part #4575
- 9" Cast Radius Corner, Part #4570
- Dual Divider, Part #2142 & 2-1/2" Dual Divider Cover, Part #2146
- Raceway Cover, Part #5112
- Socket Raceway & Cover
- Frame Support Tube, Part #2175