

Features & Benefits

The Commercial Wide Body has a hingeable frame that allows access to service the sign. The frame has provisions for Tension Clips, Corner Angles, Frame Braces and Corner Keys. Available in Mill Finish and Dark Bronze. The face material does not need to be hemmed and will not require grommets or double faced tape.

Answers to FAQ's

- Accepts up to 22 oz banner material
- Tension Clip placement Tension clips are to be placed approximately 1-1/2" from the edge of the trimmed to size face material
- Tension Clip spacing Every 5" on center
- Face material trim size Add 3" to all four sides from the outside dimension of the assembled frame. (Add a total of 6" of face material to both the height and width of the assembled frame)
- Frame Brace and Frame Support Tube placement Place every 36" on center horizontally and vertically
- •The Tension Tool that is required for this frame is Part #5135
- Add 1" to the cabinet in the direction of the lamps to allow for standard T12 bulbs to fit
- Recommended lamp spacing every 12" on center

Optional Items

- Frame Support Tube, Part #2175
- Socket Raceway
- Tension Tool, Part #5135
- Raceway Cover, Part #5116
- •6" Cast Radius Corner, Part #4525
- •9" Cast Radius Corner, Part #4520
- •8-1/2" Radius 3 Part End, Part #1673



